



FreeStyle Handheld Deactivator

The Sensormatic FreeStyle Handheld Deactivator is a battery-operated deactivator and verifier for AM EAS labels. Combining three accessories into one, this device detects active labels up to 15cm (6in), deactivates them up to 7.6cm (3in) above the surface of the unit, and when in "Search Only Mode," it verifies source tagged labels on protected merchandise. While in this mode, the handheld will not deactivate an active label.

The mobility feature allows cashiers to deactivate labels on merchandise too heavy or bulky to life onto the point-of-sale counter. This feature can also be used to address incoming/outgoing alarms at the entrance to ensure a valid purchase, and eliminate customer wait time and embarrassment.

The FreeStyle Handheld Deactivator features integrated status indicators that provide visual and audible notifications when live labels are successfully detected and deactivated. This self-contained unit utilizes internal batteries that automatically recharge when placed in charging cradle. Security passcode and time out features help prevent unauthorized use.

Retailer Values

- // Portable device detects and deactivates active AM EAS labels anywhere in the store for enhanced customer service and employee productivity
- // Automatically recharges in charging cradle to ensure device is always ready for use
- // Built-in audible and visual indicators provide immediate feedback when labels are detected and deactivated, enhancing front-end productivity
- // Security passcode and time out features help prevent authorized use

Product Codes

- ZBHHCW**
Handheld Deactivator, Base Charging Station (Customer Install-US Only)
- ZBHHCW-I**
Handheld Deactivator, Base Charging Station (Sensormatic Installed)
- ZEHHDW**
Handheld Unit
- ZEHHBCS**
Base Charging Station

Product Compatibility

All Sensormatic AM EAS Labels

Specifications

- Color** Dark Gray
- Length**
Handheld 28cm (11in)
Docking Station 20cm (8in)
- Width**
Handheld 11.4cm (4.5in)
Docking Station 14cm (5.5in)
- Height**
Handheld 3.2cm (1.25in)
Docking Station 7.6cm (3.0in)
- Weight** 0.8kg (28oz)
- Power Supply Weight** 0.8kg (28oz)

Electrical

Base Charging Station

- AC Power (N. America) 120Vac, 0.5A (60Hz) Class 2
- AC Power (Europe) 230Vac, 0.3A (50Hz) LPS

Environmental Constraints**Operating Temperature**

0°C to 40°C (32°F to 104°F)

Declarations**Deactivator and Charger****EMC**

47 CFR, FCC Part 15

Subpart C

EN55022

ETS 300 330

ETS 300 683

RS 210

Safety (second edition)

Power Supply

Certified Class 2

EN60950 LPS

UL 1950

Handheld

EN60950

UL 1950

CSA C22.2 No. 950

Charger

UL 1950

EN60950

CE This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.